

PHILIPPINE HEART CENTER East Avenue, Quezon City

SUPPLEMENTAL BID BULLETIN No. 036-2024

SUBJECT

: Revised Technical Specifications of the Project

PROJECT

: 9 units Stretcher - ITB No. 035.24

To ensure that the transactions are comparatively advantageous to the interests of the PHC, the originally pre-issued bidding documents as mentioned above, revised technical specifications is hereby introduced.

Attached - Revised Technical Specifications - Annex "A"

This Supplemental Bid Bulletin is hereby supersedes the original parameters as stated therein. All other requirements previously stated on the bid documents must be complied.

Please be guided accordingly.

Approved. Done this 16 day of May 2024, BAC Office, PHC.

ANTONIO D. PASCUAL, MD.

Chairman, BAC for Pharmaceutical Supplies and Medical Equipment



SPECIFICATION S

9 UNITS STRETCHER

Description of Function

Stretcher is used to transport patient from one place to another and received medical treatment such as IV medication, insertion prior procedure

Operational Requirements

System complete with all accessories as specified in the Technical Specifications below			
	Technical Specifications		
1	Hydraulic height adjustment		
2	Four (4) wheel casters with double locking system 2.1 Wheel diameter: 7"- 8" (non marking rubber is used for wheels to prevent casters from leaving marks on floor)		
3	Dual foot pedal control for Trendelenburg and reverse 0 to 20 degrees		
4	Stretcher body: made of stainless steel or powder coated materials		
5	Patient weight capacity: at least 250 kg.		
6	Height adjustment:		
	6.1 High position : 60 - 100 cm from the ground (bed frame only)		
	6.2 Lowest position: 24-25 cm from the ground (bed frame only)		
7	Width: Minimum - 24 inches, Maximum - 36 inches		
8	Length: Minimum- 76 inches, Maximum- 80 inches including the plastic bumpers		
9	Side rails: fixable / collapsible with double locking system for patient;s safety		
10	Power assist for fowler back rest		
11	Mattress:		
	11.1 washable and waterproof cover to keep mattress from fluid penetration		
	11.2 thickness: 3-4 inches		
12	With rubber or polymer plastic bumpers		
13	Must have the following accessories:		
	13.1 Safety belt: Push button buckle belt type (body and lower extremities) Strap type: Coated polyester vinyl, fluid resistant and can be cleaned and sanitized Strap Width: 2-3 inches Color: Black		
	13.2' Detachable tray with strap to hold monitoring devices weighing at least 5 kg.		

13.3 Compartment for patient's belongings	= 36
13.4 Control brake	
13.5 Integrated portable oxygen holder oblique (stainless), 1	1-15 cm in diameter
13.6 Adjustable IV pole *height with 2-4 hook, removable or	r collapsible
13.7 Urine bag holder	
13.8 Transport handle at head and lower part	

	Standards, Safety and Training	
14	Manufacturer/Supplier should have ISO 13485 certificate to Quality Standards	
15	With 3-year warranty for parts and services	
	Documentation	
16	User/Technical/Maintenance manuals to be supplied in English in hard and soft copies upor delivery	
17	Exclusive distributorship of similar project	
18	Delivery: 90 days	

Chief, EMP

JOYETTE ANN F. MINDORO, MPA, RN Chief, ER and Ambulatory Care/ MS1